

ATL-300P

General Features


- Engine (PERKINS 1506A-E88TAG5), Radiator 50°C max, belt driven fans, with safety guard
- 24V charge alternator
- Alternator (Stamford, Leroy Somer & Mecc Alte for option), single bearing alternator IP23, insulation class H/H
- Skid and vibration isolators
- Dry type air filter, fuel filter, oil filter
- Main line circuit breaker
- Standard control panel
- Two 12V batteries, rack and cable
- Ripple flex exhaust pipe, exhaust siphon, flange, industrial muffler

PHOTO FOR REFERENCE ONLY



Technical Data

Output Frequency	50 Hz
Rated Speed	1500RPM
Prime Power	300KVA/240KW
Standby Power	325KVA/260KW
Rated Voltage	400/230V
Phase	3
Power Factor	0.8
Fuel Consumption 100% Load	65 L/Hr
Fuel Consumption 75% Load	48 L/Hr
Fuel Consumption 50% Load	33 L/Hr
Operation Altitude	≤1000m
Ambient Temperature	≤50°C



Dimension and Weight

Genset Type	Open Frame	Soundproof
Length(L) (mm)	2915	4000
Width(W) (mm)	1210	1450
Height(H) (mm)	1600	2350
Gross Weight (kg)	2050	2850



ATL-300P

Engine Specification

Manufacturer / Model:	PERKINS 1506A-E88TAG5, 4-cycle
Air Intake System:	Turbocharged, Air/Air Cooling
Fuel System:	Direct
Cylinder Arrangement:	6 in line
Displacement:	8.8L
Bore and Stroke:	112*149 (mm)
Compression Ratio:	16.1:1
Rated RPM:	1500rpm
Max. Standby Power at Rated RPM:	293KW
Governor Type:	Electronic
Exhaust Gas Flow:	283L/S
Exhaust Temperature:	561°C
Max Back Pressure:	10kPa
Max Intake Restriction:	3.7kPa
Combustion air flow:	16.4m ³ /min
Cooling fan air flow:	370m ³ /min
Total Oil Capacity:	33.2L
Oil Consumption:	0.1% fuel consumption
Total Coolant Capacity:	41L
Thermostat:	87-98°C
Max Water Temperature:	107°C

Alternator Specification

Manufacturer / Model:	STAMFORD S4L1D-D41
Number of Phase:	3
Connecting Type:	3 Phase and 4 Wires, "Y" type connecting
Number of Bearing:	1
Protection Grade:	IP23
Exciter Type:	Brushless, self-exciting
Insulation Class, Temperature Rise:	H/H
TIF:	<50
THF:	<2%
Voltage Regulation, Steady State:	≤ ± 1%
Alternator Capacity:	310KVA
Alternator Efficiencies:	92.9%
Air Cooling Flow:	0.83m ³ /s

ATL-300P

Control System

Standard Deepsea DSE6020 Auto Mains Failure Control Panel

Manual or Auto Start Module for single genset applications.

Designed to work with electronic and non-electronic engines, providing advanced engine monitoring and protection features.

Includes a back-lit icon LCD display which shows the status of the engine at all times. Monitors engine speed, frequency, voltage and run hours and also displays the warning and shutdown status.

Includes extensive outputs and inputs making this product ideal for a wide variety of applications. It can either be programmed using the front panel or by using DSEPC software.



Optional Deepsea DSE7320 Auto Mains Failure Control Panel

Auto Mains (Utility) Failure Control Module suitable for a wide variety of single genset applications.

Displays warnings, shutdown and engine status info on the backlit LCD screen, illuminated LEDs, remote PC. Monitors the mains (utility) supply. Includes USB, RS232 and RS485 ports for system expansion.

Compatible with electronic and non-electronic engines and offers flexible inputs, outputs and engine protections to meet extensive industry requirements.

Includes enhanced event and performance monitoring, remote communication to reduce engine wear. It can either be programmed using the front panel or by using DSEPC software.



Optional Deepsea DSE8610 Auto Paralleling Control Panel

Synchronizing Auto Start Control Module for multi-genset loadshare system, designed to synchronize up to 32 gensets including electronic and non-electronic engines.

Monitors the genset and indicates operational status and fault conditions, automatically starting or stopping the engine on load demand or fault condition.

System alarms are annunciated on the LCD screen, illuminated LED and audible sounder.

Records 250 events log for maintenance. Extensive monitoring, metering and protection features are included as well as comprehensive communication and system expansion options.

Using DSE PC Software allows alteration of the operational sequences, timers, alarms with all communication ports active.





ATL-300P

Options

Engine

Water Jacket Preheater
Water Separator
Oil Pump
Oil Preheater
Battery Charger

Fuel System

Daily Fuel Tank
External Fuel Tank
Auto Fuel Filling System
Fuel Level Sensor

Control System

Auto Remote Control Panel
AMF Function Control Panel
Auto Paralleling Control Panel
Auto Transfer Switch (ATS)
ABB breaker

Alternator

Anti Condensation Heater
Permanent Magnet Generator
Winding Temp Sensor

Enclosure

Rainproof Type
Soundproof Rental Type
Mobile Type

Available Voltages

440/254V
415/240V
380/220V

Reference Standards

Generator Set: ISO 8528, CE

Engine: ISO 3046, BS 5514, DIN 6271

Alternator: BS EN 60034, IEC34, BS5000, NEMA MG1-32, VDE 0530, CSA C22.2-100, AS1359

Warranty

PT. Anugrah Teknik Listrindo memberikan garansi untuk genset selama 1 tahun atau 2000 jam mana yang dicapai terlebih dahulu.

Garansi tidak berlaku apabila :

- Uji coba baru dilakukan 3 bulan setelah barang diterima
- Uji coba tidak dilakukan oleh teknisi kami atau yang diberikuasa untuk melaksanakannya khususnya wilayah jabodetabek.
- Pembebanan melampaui batas kapasitas kemampuan.
- Akibat kesalahan pemeliharaan dan faktor alam (seperti tersambar petir, banjir, dsb).
- Garansi tidak berlaku untuk electronic, electrical parts dan instrument diluar mesin.

Kami juga memberikan pelayanan untuk jasa service maintenance sesuai dengan kebutuhan anda