

SPEKIFIKASI :

GENSET MODEL	:	YX-12
Rated Power (KW)	:	12
Max Power (KW)	:	13
Rated Current (A)	:	22,8
Rated Voltage (V)	:	220/380
Frequency (HZ)	:	50
Rated Speed (RPM)	:	1500
ENGINE MODEL	:	Y480BD
Rated Output (KW)	:	14
Governing Method	:	MECHANICAL
Bore x Stroke (mm)	:	80*90
Intaking Method	:	Natural Aspirated
Oil Volume (L)	:	7
Fuel Consumption	:	247
Fuel Consumption (L/H)	:	4
Oil Consumption (L/H)	:	1,08
Displacement L	:	1,81
Compression ratio	:	17:1
Water Volume (L)	:	10
Cooling System	:	Closed water cooled
Starting Method	:	D.C 12V or 24V electric start
	:	
ALTERNATOR MODEL	:	BC164D
Power Factor	:	0,8 lagging for 3-Phase
Phase / Connection	:	3-Phase 4-Wire connected
Excitation Method	:	Brush/Brushless Excitation
Insulation Class	:	H
Protection Class	:	IP21
Voltage Regulation	:	Automatic
CONTROL SYSTEM	:	DeepSea DSE3110
Dimension and Weight	:	
Net Weight	:	680
Dimension (m/ Open type)	:	1,350 x 0,67 x 1,03
Net Weight	:	850
Dimension (m/ Silent type)	:	1,7 x 0,9 x 1,15



**Spesifikasi dapat berubah sewaktu-waktu*